
ZOTAC H67-ITX WiFi Supreme (LGA1155) [H67ITX-C-E]

[http://www.cartft.com/catalog/il/1488]



Product Name



114.95 EUR incl. 19% VAT, plus shipping

Assemble the perfect small form factor system for all your computing demands with the flexible ZOTAC® H67-ITX WiFi mini-ITX platform. The ZOTAC® H67-ITX WiFi supports socket LGA1155 2nd generation Intel® Core™ family processors with turbocharged Intel® HD Graphics to let users select the perfect amount of processing power for their needs – whether it is dual or quad-core, with or without Intel® HyperThreading™ technology.

Demanding gamers can install a standard PCI Express x16 ZOTAC® graphics card in the H67-ITX WiFi to form a perfect miniature gaming PC that delivers big system power in a miniature form factor. A mix of seven total SATA 6.0 Gb/s, SATA 3.0 Gb/s and eSATA ports with RAID 0, 1, 5 and 10 support on the ZOTAC® H67-ITX WiFi enable users to maximize storage connectivity and complete the ultimate home theatre PC or home file server.

Product Name	ZÖTAC H67-ITX WiFi
Model	
Model	H67ITX-C-E
Chipset	
Manufacturer	Intel
Chipset	H67 Express (B3)
GPU	Intel® HD Graphics ready
CPU Compatibility	
Name	2nd Generation Intel® Core™ i3
	i5 & i7 Intel® HD Graphics 2000/3000 ready
Socket	LGA1155
Bus	N/A
Memory	
Memory Type	DDR3
Memory Speed	1066/1333 MHz
Slots	2 x 240-pin DIMM
Capacity	Up to 16GB
CPU and Memory Compatibility List	
CPU and Memory Compatibility List	see above
3D API	
DirectX	DirectX® 10.1
OpenGL	OpenGL® 2.1
Expansion	
Slots	1 x PCI Express x16

CARTFT. COM Shop for mobils PC- and GP9-Solutions

ZOTAC H67-ITX WiFi Supreme (LGA1155) [H67ITX-C-E]

[http://www.cartft.com/catalog/il/1488]

Networking	
Ethernet	10/100/1000Mbps
WiFi	802.11n/g/b (300Mb/s)

Audio

AN/Alog 8-ch HD

Digital Optical S/PDIF and HDMI outputs

Ports

DVI 1 (HDCP)

HDMI 1 (1080p w/8-ch audio)

Display Port 1

VGA 1 (w/Adapter)
SATA 2 (SATA 6.0 Gb/s)

4 SATA 3.0 Gb/s (w/RAID 0 / 1 / 0+1 / 5)

eSATA 1 (SATA 3.0 Gb/s)

 PATA
 N/A

 PS/2
 1

 Serial Port
 N/A

USB Ports 8 x USB 2.0 (4 on back panel / 4 via pin header)

4 x USB 3.0 (2 onback panel / 2 via pin header) 8 USB 2.0 ports (4 on back panel / 4 via header)

FireWire Ports N/A

Cooler

Cooler Passive (no fan)

Form Factor mini-ITX

OS Compatibility

Windows® Vista / 7 Premum ready

General

SLI Supported No

Maximum Resolution 2048 x 1536

Other

Wake-On Support Wake-on USB

Wake-on-LAN

Overclocking features No

Packaging

Package Contents 4 x SATA cables

1 x 4-pin CPU power extension cable

1 x DVI-to-VGA adapter 1 x I/O back plate

2 x WiFi antennas

1 x USB 3.0 header (full-size bracket)

1 x USB 3.0 low-profile bracket

Graphics Output 1 DVI / 1 HDMI / 1VGA / 1 DP