

298.00 EUR  
incl. 19% VAT, plus [shipping](#)



- Intel Celeron Processor BayTrail-M N2910/N2920
- 2 \*DDR3L 1066MHz Single CH SO-DIMM up to 8GB
- Support 2 \* Serial ATAll (3Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 2-CH
- Integrated 1 \* 24-bits Dual CH LVDS
- Supports 1 \* Realtek RT8111G Gigabit LAN
- Support CPU Smart FAN
- Support Watch dog Technology
- Thin Mini-ITX Form Factor(17cm x 17cm)
- Slim & Fanless design, within 2cm height

<b>CPU</b>	• Intel Celeron Processor BayTrail-M N2910/N2920
<b>Chipset</b>	• INTEL® Bay Trail-M SoC Processor
<b>Memory</b>	• 2 *DDR3L 1333/1066MHz Single CH SO-DIMM up to 8GB
<b>Expansion Slots</b>	• 1 * PCI-E x 1 slot • 1 * MINI PCI-E
<b>Storage</b>	• 2 * Serial ATAll (3Gb/s) connectors (One share with mSATA) • 1 * mSATA socket (Share with one SATA port)
<b>Audio</b>	• Realtek ALC662 2-Channel HD Audio
<b>Ethernet LAN</b>	• 1 * RTL8111G PCI-E Gigabit LAN
<b>LVDS</b>	• 1 * 24-bits Dual CH LVDS connector
<b>USB</b>	• Embedded 3 * USB 3.0 + 5 * USB 2.0/1.1
<b>Special Features</b>	• Support ACPI S3 • Support CPU Smart FAN • Support Watch Dog
<b>Rear Panel I/O</b>	• 1 * USB 3.0 port • 3 * USB 2.0/1.1 ports • 1 * RJ-45 port • 1 * DVI-I port • 1 * COM port (Support RS232/422/485) • 1 * Line-out connector • 1 * 4-pin 9V~36V DC in jack

• <b>Internal I/O</b>	<ul style="list-style-type: none"> <li>• 1 * USB 3.0 header for 2 USB 3.0 ports</li> <li>• 1 * USB 2.0/1.1 header for 2 USB 2.0 ports</li> <li>• 1 * KB/MS header</li> <li>• CPU smart Fan / System Fan headers</li> <li>• 1 * LVDS header &amp; 1 * GPIO header &amp; 1 Parallel header</li> <li>• 3 * COM headers &amp; 4 * COM ports 5V/12V Selectable headers</li> <li>• 1 * AUDIO AMP &amp; 1 * AUDIO header &amp; 1 * SPDIF header</li> <li>• 1 * chassis intrusion header &amp; 1 * AT mode selectable header</li> </ul>
• <b>BIOS</b>	• AMI 64MB SMT Flash ROM
• <b>Form Factor</b>	• Thin Mini ITX Form Factor (170mm x 170mm)
• <b>Functional</b>	• Panel PC, ATM, Security, KIOSK, POS, General Application, Transportation
• <b>Certificate</b>	• CE, FCC, RoHS
• <b>Temperature</b>	<ul style="list-style-type: none"> <li>• Operating within 0~60 centigrade</li> <li>• Storage within -20-85 centigrade</li> </ul>