



299.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel® Q87 Express Chipset
- Supports Intel LGA 1150 Socket Core™ i3, i5, i7 & Pentium Processors
- Support 4 * 240 pin 1600/1333MHz Dual CH DDR3 SDRAM DIMM Max. to 32GB
- Intel 82574L & I217LM Gigabit LAN
- Intel Active Management Technology (iAMT 9.0)
- Support TPM 1.2 function
- Support CPU Smart FAN
- Supports ACPI S3 Function
- Support Watch dog Technology
- mATX form factor ■244mm * 244mm■

• CPU	INTEL® LGA 1150 Socket Core i7/i5/i3/Pentium Processor
• Chipset	INTEL® Q87 Chipset
• Memory	4 * 240 pin 8GB 1600/1333/1066 Dual CH DDR3 SDRAM DIMM Max. up to 32GB
• Expansion Slots	1 * PCIe x 16, 2 * PCI, 1 * PCIe x 4 1 * full size MINI PCI-E socket (Selectable with mSATA)
• Storage	5 * Serial ATA3 6Gb/s connectors support RAID 0, 1, 5, 10
• Audio	Realtek ALC662 6-Channel HD Audio CODEC
• Ethernet LAN	Intel 82574L & I217LM PCI-E Gigabit Ethernet LAN
• USB	Embedded 4 * USB 3.0 + 8 * USB 2.0/1.1
• Special Features	Support ACPI S3 Support CPU Smart FAN Support Watch Dog

• Rear Panel I / O	2 * USB 3.0 ports 4 * USB 2.0/1.1 ports 2 * RJ-45 ports 1 * COM port (Support RS232/422/485) 1 * VGA & 1 * DVI-D & 1 * HDMI port & 1 * DP port 3 * Audio Phone Jack
• Internal I / O	1 * USB 3.0 header for 2 USB 3.0 ports 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports CPU /NB / Chassis Fan connectors 1 * KB/MS headers 1 * GPIO header 9 * COM header (COM2 support RS232/422/485) 1 * TPM 1.2 header 1 * CIR header 1 * Chassis Intrusion header 1 * AUDIO header 1 * 24-pin & 8-pin 12V ATX Power connector
• BIOS	AMI EFI 64MB DIP Flash ROM
• Form Factor	Micro ATX form factor ■ 244mm x 244mm ■
• Functional	ATM, Automation, Medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation
• Certificate	CE, FCC, RoHS
• Temperature	Operating within 0-60 centigrade Storage within -20-85 centigrade