

339.00 EUR

incl. 19% VAT, plus [shipping](#)

- For Celeron M 1.5Ghz
- FANLESS carpc system
- 12VDC based !
- Closed front !



CARTFT.COM



Support:  [Assembling Tutorial \[DE\]](#) |  [Assembling Tutorial \[EN\]](#)

Fanless CarPC-barebone for use with Intel P4/Celeron M CPU.

Celeron-M 1.7Ghz is recommended for fanless operation.

CALU specifications	
Processor (supported)	Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher
Memory	Supports DDR 333/266 DIMM RAM 0.8" low profile 2x memory slots ! Maximum : 2 GB
Video	Intel Extreme Graphics 2 Supports up to 64MB DVMT video memory
Audio	Software AC '97 Audio CODEC

Peripheral Connection

Front :

1 x IEEE 1394 Firewire port

1 x USB 2.0 / 1.1 Port

1 x MIC Port

1 x Ear Phone output Jack

Power-on button

Reset button

Power-on and HDD LED

Rear :

1 x RS232 COM port

1 x parallel printer port

1 x RJ45 10/100Mb Fast Ethernet

1 x Line-Out output Jack

2 x USB 2.0 / 1.1 Ports

1 x 15 pin VGA

1 x 12v DC Power Jack input

Storage

One 2.5 inch Hard Disk and 9.5mm high.

(Support Ultra DMA 33/66/100).

Weight & Size

System approximately 3kg (fully equipped).

System Dimension: 155 x 255 x 55 mm

Power req.

12V, 5A

Accessory**Storage**

Supports all 2.5" standard IDE hard drive, ATA-100/66/33.

Scope of supply

110V/230V EU power supply

Barebone

CPU Kühlkörper

Graphics driver for 800x480 resolution : [Here](#)