

TE Connectivity VFQ69383B21JN-518L (vehicle roof antenna, 3x SMA male 5m, 3G/4G/5G/ISM/CBRS, WIFI/BT)

[http://www.cartft.com/catalog/il/3807]



169.00 EUR

incl. 19% VAT, plus shipping

- GPS/GLONASS/GSM/4G/5G!
- WLAN / Bluetooth!
- Active antenna!
- · SMA connectors!

Support: Specifications

The Gar VFQ69383x21JN VFQ69383B21JN-518L multiport/multiband antenna provides an excellent solution for public safety, transportation, and aftermarket fleet applications. Configured for two-port operation over the 3G/4G/5G/ISM/CBRS bands and oneport operation over the low//high frequency Wi-Fi bands. An additional fourth port provides an active antenna for enabling GNSS global navigation services.

FEATURES AND BENEFITS

- One single-hole mount/fixing reduces vehicle damage and the cost of installation
- Attractive IP67 low profile aerodynamic housing
- Multiband/multiport operation with GNSS navigation
- Operates well on a ground plane and without a ground plane.

APPLICATIONS

- FirstNet/Public safety
- Transportation
- Aftermarket fleet



TE Connectivity VFQ69383B21JN-518L (vehicle roof antenna, 3x SMA male 5m, 3G/4G/5G/ISM/CBRS, WIFI/BT)

[http://www.cartft.com/catalog/il/3807]

• 5G-ready

• Rugged LTE gateways

• Others

Antennen Model VFP69383B22JN-518J

Port Configuration 2x 3G/4G/5G/ISM/CBRS, 2x WIFI

Watchdog Timer Support, Offer 1 – 255 Step

Operating Frequency (Mhz) 698-806 / 824-894 / 880-960 / 1690-3800 / 2400-2500 / 4900-6000

Azimuth Plane 3db

Beamwidth 360° Omnidirectional

Nominal IMpedance (ohms) 50

Polarization Linear Vertical Max Power - Ambient 25°C 10 Watts

Mechanical Secifications

Dimensions 179x63x48 mm / 0,63 kg

CableType LMR 100, Black

Mounting P-Mount Baseplate. Aluminium

Enviremental Specifications

Operating Environment Outdoor Vehicle / IP67

Operating Temperature: -30 to +70°C

Temperatures

Storage Temperature: -40 to +85°C

Material Substance

Compliance

RoHS