



999.00 EUR
incl. 19% VAT, plus [shipping](#)

- HDMI !
- HDTV !

- VIA CX700M Single chipset Technology
- Support Front Side Bus 533MHz
- Support 2 Serial ATA 2 Devices with RAID 0, 1
- Support PCI 120-Pin Adapter Conn. With Expansion Daughter-boards
- Gigabit Ethernet LAN Supported
- 6 Channel HD Audio CODEC
- VIA VT6307 IEEE1394a Controller
- VIA VT1622A TV Encoder
- 17 x 17CM Mini-ITX Form Factor

| | |
|-----------------------------|--|
| Form Factor | Mini-ITX Express Motherboard |
| CPU | VIA C7 1.2 GHZ CPU |
| Memory | 1 * 240-pin DIMM Sockets for DDR2 533 up to 1 GB |
| Chipset | VIA CX700M Single Chipset |
| Power Management | ACPI S3 Compliant ,supports power saving mode |
| PCI enhanced IDE | 2* Ultra DMA 133 / 100 / 66 IDE Devices Support |
| Serial ATA Interface | 2 Serial ATA2 HDDs with RAID 0, 1 Function Support |
| VGA Interface | VIA Unichrome Pro II |
| Video Memory | Share Memory up to 128MB |
| Audio Interface | VIA VT1708A 6-Channel HD Audio CODEC |
| LAN Interface | VIA VT6122 10 / 100 / 1000 PCI LAN |
| Extended Interface | 1 * 32-bit PCI Slot |
| | 1 * PCI 120-Pin Adapter Connector with Expansion Daughter Boards |
| Internal I/O Port | 2 * High Speed USB Connectors for 4 USB 2.0 Ports 1 * CPU Smart Fan Connector, 2 * Chassis Fan Connectors 2 * 9-Pin COM Port Connector 1 * CD / AUX Audio in & SPEAK Out 1 * HDTV Out Connector 1 * IrDA (SIR) 1 * 6-pin Video Input Pin-header 1 * PCI 120-Pin Adapter Conn. |

| | |
|--------------------------|---|
| External I/O Port | 2 * High Speed USB Connectors @ 480 M-bit / s 1 * D-Sub 15-pin VGA Connector 1 * HDMI Port 1 * PS / 2 Mouse & 1 * PS/2 Keyboard 1 * RJ45 Connector 1 * Audio I / O 1 * IEEE 1394a Connector |
| BIOS | Award 4 MB Flash ROM |
| Power Requirement | Standard 24-Pin ATX Power supply |
| Dimension | 170mm x 170mm |